

KEY FEATURES

- Fully complies to IS 2189 & tested by ERTL (N)
- Operates on 220V AC, 50Hz AC Supply
- 16*2 line dot matrix LCD
- Zone wise fire, open, short LED Indications
- External s/w to test each zone fire, open, short status manually
- External s/w for reset, silence, lamp test
- Zone isolation facility with zone voltage cutoff
- Relay for free contacts
- Mains on, system on, charger on visual indications
- battery low & common fire indications
- Auto dialer attachable facility
- Enough inside space for SMF battery
- Compatible with all types of fire detectors
- Maximum 25 nos. detectors in each zone
- Hooter output current can be increased as per customer requirement.

TECHNICAL DATA

- Operating Voltage	AC 220v 50Hz ±10%, DC 24v 1 amp
- Operating Temperature	0°C to 50°C
- Operating Humidity	95% (non-condensing)
- Hooter Output	1 A (24v DC)
- EOL	4k7 ohm, 1 per zone
- Weight	4.5 kg
- Construction	1.8 mm CRCA sheet duly power coated
- Dimension	H 272mm * W 346mm * D 96mm
- Colour	Caramel White

02 & 04 ZONE FIRE ALARM PANELS



MODEL NO. : QT 02QFP



MODEL NO. : QT 04QFP

KEY FEATURES

02 & 04 ZONE FIRE ALARM PANELS WITH INBUILT DIALER

- Fully complies to IS 2189 & tested by ERTL (N)
- Operates on 220V AC, 50Hz AC Supply
- 16*2 line dot matrix LCD
- Battery backup with inbuilt charger + Relay for free contacts
- Operates on both tone and pulse with User password protection
- External s/w to test each zone fire, open, short, reset, silence, lamp test status manually
- Zone isolation facility with zone voltage cutoff
- Mains on, system on, charger on visual indications
- Enough inside space for SMF battery
- Compatible with all types of fire detectors, Maximum 25 nos. detectors in each zone
- Speech dialer facility with 06 telephone nos. and 01 no. message.
- 30 sec. duration time of voice message and Hooter time 0 to 7 min
- Entered telephone nos. and messages check facility.
- Operates on both DOT and EPABX + Telephone nos. editing facility.
- All programming and enter telephone nos. through keypad.
- Programmable redial option (01 - 03 times)
- Fire/Fault status in unambiguous coloured LED indications.
- Zone wise fire, common fire, Open, Short LED, battery low indications.

TECHNICAL DATA

- Operating Voltage	AC 220v 50Hz ±10%, DC 24v 1 amp
- Operating Temperature	0°C to 50°C
- Operating Humidity	95% (non-condensing)
- Hooter Output	1 A (24v DC)
- EOL	4k7 ohm, 1 per zone
- Weight	4.5 kg
- Construction	1.8 mm CRCA sheet duly power coated
- Dimension	H 272mm * W 346mm * D 96mm
- Colour	Caramel White



MODEL NO. : QT 02QFDP



MODEL NO. : QT 04QFDP

NOTE : Inbuilt autodialer panels are available in two variant only i.e. 02 zone and 04 zone.

